

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 010 452 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
21.06.2000 Bulletin 2000/25

(51) Int. Cl.⁷: B01D 53/26

(21) Application number: 98204242.6

(22) Date of filing: 14.12.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor:
Lang, Kristian Karl Henrik
1410 Waterloo (BE)

(71) Applicant:
ATLAS COPCO AIRPOWER N.V.
2610 Wilrijk (BE)

(74) Representative: Donné, Eddy
Bureau M.F.J. Bockstael nv
Arenbergstraat 13
2000 Antwerpen (BE)

(54) Method and device for drying a gas

(57) Method for drying a gas by means of adsorption on a regenerable desiccant (11), whereby a portion of the dried gas is used for regenerating the desiccant. The gas portion used for the regeneration is heated in at least two successive steps, said steps being performed in different zones (30,31 or 33-36) situated successively in the flow direction of the gas portion through the regenerating desiccant (11) and by stopping the heating in a zone (30,31 or 33-36) as soon as the desiccant (11) in this zone (30,31 or 33-36) is regenerated, so that this zone (30,31 or 33-36) may already be cooled down by the gas portion for regeneration while a successive zone (30,31 or 33-36) is still being regenerated by the heated gas. In each vessel (7,8) there are at least two individually controllable heating elements (25-26;27-28;38-41).




Fig. 2

EP 1 010 452 A1

Description

[0001] This invention relates to a method for drying a gas by means of adsorption on a regenerable desiccant, according to which method a gas is sent through a first amount of this desiccant, while a portion of the dried gas is sent through a second amount of already used desiccant for regenerating it, this gas portion for the regeneration being heated and after having taken up moisture is evacuated, whereby, after regenerating the second amount of desiccant, the gas flow is inversed so that the gas to be dried is sent through the regenerated second amount of desiccant, while a portion of the dried gas is now sent through the first amount for regenerating.

[0002] Methods of this kind are used amongst others for drying compressed gas, mostly compressed air. The compressed gas leaving the compressor has a relatively high moisture content. Part of the moisture is separated by cooling this air. The remaining moisture may be disadvantageous for the conducts and is undesirable for some applications.

[0003] A known method of this kind is disclosed amongst others in EP-A-0.419.433. The compressed air to be dried is dried in a first column, while the wet desiccant is regenerated in a second column by a portion of the dried compressed air. This portion is introduced, at half-height of the column, in the lower end of a tube mounted axially in the column and containing an electrical heating element. The gas is heated in the tube and flows in the wet desiccant at the top of the column, flows downwardly and leaves, charged with moisture, the column at the bottom.

[0004] It is evident that this heated gas causes a heating of the desiccant. Heated desiccant is however less effective than cold desiccant and therefore the regenerated desiccant is normally cooled before being used again for drying. If the desiccant is too hot when it is used for drying, a regeneration will start instead of drying. Cooling is also necessary to avoid dew point pikes during drying.

[0005] In said known method, this cooling is obtained by turning off the electrical heating while a portion of the dried compressed air is still sent through the desiccant.

[0006] In this way, the cooling can only take place after the complete regeneration of the desiccant and consequently the complete regeneration and cooling process is time-consuming. Moreover, an additional amount of already dried air is required for the cooling and is lost for consumption. This increases the energy consumption.

[0007] The invention seeks to provide a method for drying a gas avoiding said disadvantages and permitting to minimize the energy consumption for regenerating the desiccant.

[0008] In accordance with the invention, this object is accomplished by heating the gas portion used for the

regeneration in at least two successive steps, said steps being performed in different zones situated successively in the flow direction of the gas portion through the regenerating desiccant and by stopping the heating in a zone as soon as the desiccant in this zone is regenerated, so that this zone may already cool down by the gas portion for regeneration while a successive zone is still regenerated by the heated gas.

[0009] It is obvious that the first zone to be regenerated will be the zone where the gas portion for regeneration is entered as this gas portion has not yet taken up much moisture.

[0010] This is especially the case if the gas portion for regeneration is sent through an amount of desiccant in the opposite direction as the gas to be dried was sent when this amount was used for drying.

[0011] In this case said first zone is the zone which has taken up the less of moisture during drying.

[0012] The number of heating steps and consequently zones during regeneration may be higher than two.

[0013] Heating of the zones of the amount of desiccant which is regenerated may be performed in several ways, for example by electrical heating elements, but a very effective way of heating is by means of micro-waves.

[0014] The invention also relates to a device which is especially suitable for applying the method according to either one of the preceding embodiments.

[0015] The invention concerns consequently a device for drying gas by adsorption, comprising an inlet pipe for the wet gas, an outlet pipe for the dried gas en between them at least two vessels mounted in parallel filled with a regenerable desiccant, means for connecting the inlet pipe alternately with the inlet of one of the vessels and the inlet of the other vessel for drying the wet gas, means for returning a portion of the dried gas to the vessel which is not connected to the inlet pipe, for the regeneration of the desiccant and heating means in both vessels, characterized in that the heating means in each vessel comprised several, individually controllable heating elements which are situated successively in the flow direction of the gas through the vessel.

[0016] The invention will now be described by way of example and with reference to the accompanying drawings in which:

Figure 1 shows schematically a compressor installation possessing a device for drying gas according to the invention;

Figure 2 shows schematically the device for drying gas from the installation of figure 1;

Figure 3 shows a part of the device of figure 2, but on a larger scale and with respect to another embodiment of the invention;

Figure 4 is a cross-section according to line IV-IV in figure 3.

[0017] Figure 1 shows a compressor installation which comprises essentially a compressor 1 and in the compressed air conduit 2 of it successively an after cooler 3, a pressure vessel 4, an oil separator 5 and a drying device formed by an adsorption dryer 6.

[0018] As shown more in detail in figure 2, this adsorption dryer 6 comprises two columns or upstanding vessels 7 and 8 which are mounted in parallel between the inlet pipe 9 and an outlet pipe 10 and which are filled with a desiccant 11, for example silicagel.

[0019] The inlet pipe 9 consists of the portion situated before the vessels 7 and 8 of the compressed air conduit 2 and is connected by means of a first electrically controlled three-way valve 12 and one of two conduits 13 and 14 connected thereto, with respectively the vessel 7 or the vessel 8.

[0020] The outlet pipe 10 consists of the portion situated after the vessels 7 and 8 of the compressed air conduit 2 and is connected by means of two conduits 15 and 16 with respectively the vessels 7 and 8.

[0021] In the conduit 15 a non-return valve 17 is mounted while in the conduit 16 a non-return valve 18 is mounted. Both non-return valves 17 and 18 prevent the gas to return to the vessel 7 or 8.

[0022] In a variant, the two non-return valves 17 and 18 may be replaced by a single three-way valve.

[0023] Both non-return valves 17 and 18 are shunted by a conduit 19 containing a throttle valve 20.

[0024] To conduits 13 and 14 is connected an air outlet pipe 21 or 22 which is closable by a valve 23 or 24.

[0025] In each of the vessels 7 and 8, heating means are mounted which each consist of a number, in the given example two, heating elements distributed over the height of the vessels in different zones.

[0026] Vessel 7 contains thus two heating elements 25 and 26, more particularly electrical resistances, while vessel 8 contains two heating elements 27 and 28, more particularly electrical resistances.

[0027] The uppermost heating elements 25 and 27 are mounted inside an axially extending tube 29 which is perforated at the top of the vessel 7 or 8 and which is connected with its lower end, approximately at half-height of the vessel 7 or 8, with the conduit 15 or 16.

[0028] The tube 29 opens with its perforations on the upper zone 30 of the vessel 7 or 8.

[0029] The heating elements 26 and 28 are situated directly in the desiccant 11 in the lower zone 31 of the vessel 7 or 8.

[0030] The heating elements 25, 26, 27 and 28 may be individually switched on or off by means of a control device 34.

[0031] Both non-return valves 17 and 18 are shunted together by a conduit 32 closable by a valve 33 also controllable by said control device 34.

[0032] Said control device 34 also controls the electrical valves 23 and 24 and the three-way valve 12.

[0033] The above-mentioned device operates as

follows:

[0034] The compressed air produced by the compressor 1 is cooled in the after cooler 3 and accumulated in the pressure vessel 4 where it is further cooled. As a result, part of the moisture in the compressed air will compensate. The condensate is separated in a manner not shown in the figure 1.

[0035] After separation of the oil in the oil separator 5, the compressed air enters via the inlet pipe 9 in the adsorption dryer 6.

[0036] When the three-way valve 12 is in the position shown in figure 2, the compressed air enters via the conduit 13 in the vessel 7 where remaining moisture of the air is adsorbed in the desiccant 11.

[0037] The heating elements 25 and 26 are switched off and the valve 23 is closed.

[0038] The dried air leaves the vessel 7 through the tube 29 and the conduit 15 and reaches through the non-return valve 17 the outlet pipe 10. The non-return valve 18 prevents the air to enter the conduit 16.

[0039] A small portion, for instance 3 to 8 vol. % of the dried air, however, reaches the conduit 16 through the shunt conduit 19, as far as the desiccant 11 in vessel 8 has already been used for drying and is saturated with moisture.

[0040] This portion of the dried air expands in the tube 29 in the vessel 8. The heating elements 27 and 28 are switched on by the control device 34 and the valve 24 is opened.

[0041] The air portion is first heated by the heating element 27 up to a temperature between 120 to 250°C, enters the upper zone 30 and flows downwards through the desiccant 11. This portion of air is further heated by the heating element 28 in the lower zone 31.

[0042] Due to the heated air, the desiccant 11 in the vessel 8 is regenerated. The heating element 28 prevents condensation of the moisture with which the air portion has been saturated in the zone 30 and permits taking up of more moisture by the air because of its higher temperature.

[0043] The regenerating air charged with moisture is evacuated through the outlet pipe 22 in which the valve 24 is open.

[0044] The air portion for regenerating will first take up moisture from top. The dryer the top, the more the air can take up moisture from a lower layer of desiccant 11. The desiccant 11 in the upper zone 30 will be dry and thus regenerated before the desiccant 11 in the lower zone 31.

[0045] This is the more the fact that, as during drying with the desiccant 11, the wet air flows from bottom to top, the desiccant 11 in the lower zone 31 contains more moisture than the desiccant 11 in the upper zone 30 when the regeneration starts.

[0046] After a certain time, namely when the desiccant 11 in the upper zone 30 is expected to be dry, or preferably after a sensor measuring the degree of moisture in this zone 30 shows that the desiccant 11 in this

zone 30 is dry, the control device 34 switches off the heating element 27.

[0047] This moisture content may be measured indirectly by measuring the temperature. When the temperature of the air at the lower end of zone 30 reaches its maximum situated between 150 and 200°C, there is no water to be taken up from the desiccant 11 in this zone 30.

[0048] This means that the air portion for the regeneration cools the desiccant 11 in the upper zone 30 which was previously heated, while the air in the lower zone 31 is still heated by the heating element 28 and still dries the desiccant 11 in this zone 31.

[0049] When also the desiccant 11 in this zone 31 is dry, which can be detected by measuring the temperature at the outlet of zone 31, the control device 34 switches off the heating element 28 and the zone 31 is cooled. Finally the valve 24 is closed.

[0050] When the desiccant 11 in the vessel 7 is no longer effective and must be regenerated, the control device 34 changes the position of the three-way valve 12 so that the pipe 9 is now connected with the conduit 13. The regenerated desiccant 11 in the vessel 8 is now used for drying, while the desiccant 11 in the vessel 7 is regenerated in exactly the same manner as described herebefore for the desiccant 11 in the vessel 8. At the start of the regeneration, the valve 23 is opened so that the pressure can be relieved from the vessel 7 and the regeneration may be performed at ambient pressure.

[0051] As at the end of the regeneration, the upper zone 30 is already cooled while the lower zone 31 is still being regenerated, the total cooling time of the regenerated desiccant 11 is shortened.

[0052] This permits to use a smaller quantity of desiccant 11 in each vessel 7 and 8 and a smaller vessel. Moreover, the radiation heat losses from the regenerating vessel are smaller and the energy consumption is lower.

[0053] It is obvious that the number of zones 30 and 31 and thus the number of heating elements 25,26 or 27,28 in each vessel 7 or 8 may be more than two. Also other heating means than electric heating elements may be used as well.

[0054] In figures 3 and 4 another embodiment of the adsorption dryer 6 is shown, whereby this dryer 6 only differs from the above described dryer 6 in that the vessels 7 and 8 are different in construction, more precisely in that these vessels 7 and 8 are divided in five zones 33, 34, 35, 36 and 37, four of which can be heated individually by means of a microwave heat source 38, 39, 40 or 41.

[0055] Only a part of the dryer 6 comprising the vessel 7 has been shown, but the vessel 8 is identical.

[0056] Each microwave heat source 38 to 41 consists of a generator 42 mounted on the outside of the vessel 7 and an antenna 43 extending inside one of the zones 33 to 36 to be heated. The lowermost zone 37 is

not provided with heating means.

[0057] Each zone 33 to 36 contains also a sensor 44 detecting the moisture content in the zone and connected via the control device 34 with the generator 42 of the microwave heat source 38, 39, 40 or 41 pertaining to this zone.

[0058] The zones 33 to 37 are separated from each other by metallic perforated screens 45 restraining the microwaves emitted by a heat source 38 to 41 within the corresponding zone. The screens 45 are for instance from stainless steel.

[0059] The perforations of the screens 45 have for instance a diameter of about 1 mm while the desiccant particles are beads with a diameter between 2 and 5 mm, so that the screens 45 not only retain the microwaves but also the desiccant 11.

[0060] The screens 45 are conical in order to distribute the desiccant 11 over the whole diameter of the vessel 7 and to obtain a filling of the desiccant 11 without pockets.

[0061] In order to permit filling and emptying the vessel 7 with desiccant 11, the screens 45 are provided with an opening 46 at their top, for instance a round opening 46 with a diameter of about 2 cm, and a number of slots 47 at their lower edge, for instance four triangular slots 47.

[0062] Moreover, the vessel 7 is provided with two filling plugs 48 at its top and two emptying plugs 49 at its bottom.

[0063] A purge pipe 50 with a purge air nozzle 51 is connected to the conduit 15.

[0064] The drying device operates in the same way as described herebefore except that during the regeneration of the desiccant 11, the heating of the air portion for the regeneration takes successively place in four zones 33 to 36 by microwaves, whereby as soon as a sensor 44 detects that the desiccant 11 in its zone is dry, the microwave generator 42 heating this zone is shutt off.

[0065] The zones 33 to 36 will successively from top to bottom be dry and consequently no longer heated but cooled by the air portion for the regenerating.

[0066] Filling with desiccant 11 takes place by opening the filling plugs 48 and pouring desiccant 11 in the vessel 7. The desiccant 11 falls through the slots 47 and the opening 46 of a screen 45 and fills up each zone 33 to 37.

[0067] Emptying for replacing the desiccant 11 occurs by removing the emptying plugs 49, whereby the desiccant 11 falls down through the openings 46 and slots 47.

Claims

1. Method for drying a gas by means of adsorption on a regenerable desiccant (11), according to which method a gas is sent through a first amount of this desiccant (11), while a portion of the dried gas is

- sent through a second amount of already used desiccant (11) for regenerating it, this gas portion for the regeneration being heated and after having taken up moisture is evacuated, whereby, after regenerating the second amount of desiccant (11), the gas flow is inverted so that the gas to be dried is sent through the regenerated second amount of desiccant (11), while a portion of the dried gas is now sent through the first amount for regenerating, characterized in that the gas portion used for the regeneration is heated in at least two successive steps, said steps being performed in different zones (30,31 or 33-36) situated successively in the flow direction of the gas portion through the regenerating desiccant (11) and by stopping the heating in a zone (30,31 or 33-36) as soon as the desiccant (11) in this zone (30,31 or 33-36) is regenerated, so that this zone (30,31 or 33-36) may already cool down by the gas portion for regeneration while a successive zone (30,31 or 33-36) is still regenerated by the heated gas.
2. Method according to claim 1, characterized in that during the regeneration, heating of the gas occurs by means of microwaves.
3. Device for drying gas by adsorption, comprising an inlet pipe (9) for the wet gas, an outlet pipe (10) for the dried gas and between them at least two vessels (7,8) mounted in parallel filled with a regenerable desiccant (11), means for connecting the inlet pipe (9) alternately with the inlet of one of the vessels (7,8) and the inlet of the other vessel (8,7) for drying the wet gas, means for returning a portion of the dried gas to the vessel (7,8) which is not connected to the inlet pipe (9), for the regeneration of the desiccant (11) and heating means in both vessels (7,8), characterized in that the heating means in each vessel (7,8) comprised several, individually controllable heating elements (25,26; 27,28; 38-41) which are situated successively in the flow direction of the gas through the vessel (7,8).
4. Device according to claim 3, characterized in that the vessel (7,8) is divided in more than two zones (33-36) which are heatable by means of a heating element (38-41).
5. Device according to claim 3 or 4, characterized in that in each zone (33-36) provided with a heating element (38-41) is also mounted a moisture sensor (44) commanding through the intermediary of a control device (34) the heating element (38-41).
6. Device according to either one of claims 3 to 5, characterized in that the heating elements are microwave sources (38-41).
7. Device according to claim 6, characterized in that the vessels (7,8) are separated in at least two zones (33,34,35,36,37) by means of at least one perforated screen (45).
8. Device according to claim 7, characterized in that the screen (45) is conical.
9. Device according to claim 8, characterized in that each screen (45) is provided with an opening (46) at its top and with at least one slot (47) at its lower edge.
10. Device according to claim 9, characterized in that each vessel (7,8) comprises at least one filling plug (48) at its top and at least one emptying plug (49) at its bottom.




Fig. 1




Fig. 2




Fig. 3




Fig. 4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 4242

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 485 686 A (C. F. SEARS ET AL) 23 January 1996 * column 4, line 25 - column 6, line 45 *	3,6	B01D53/26
A	---	1,2	
A	US 4 127 395 A (P. M. MCKEY ET AL) 28 November 1978 * column 8, line 56 - column 13, line 31 *	1,3,5,10	
A	EP 0 100 107 A (PALL CORPORATION) 8 February 1984 * page 26, line 8 - page 30, line 18 *	1,3	
A	US 5 581 903 A (L. A. BOTICH) 10 December 1996 * column 3, line 5 - column 7, line 50 *	1-3,6	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B01D
Place of search THE HAGUE		Date of completion of the search 20 April 1999	Examiner Doolan, G
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03/92 (Pou0311)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 4242

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-04-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5485686 A	23-01-1996	DE 19602131 A	24-07-1997
US 4127395 A	28-11-1978	AT 370340 B	25-03-1983
		AT 742177 A	15-08-1982
		BE 859837 A	18-04-1978
		BR 7706937 A	08-08-1978
		CA 1085747 A	16-09-1980
		CH 635247 A	31-03-1983
		DE 2746204 A	20-04-1978
		DK 462577 A, B,	19-04-1978
		FI 773061 A	19-04-1978
		FR 2367530 A	12-05-1978
		GB 1553780 A	10-10-1979
		IN 147180 A	08-12-1979
		JP 1127004 C	14-12-1982
		JP 53083983 A	24-07-1978
		JP 57018933 B	20-04-1982
		NL 7711379 A	20-04-1978
		PT 67166 A, B	01-11-1977
		SE 435022 B	03-09-1984
		SE 7711650 A	19-04-1978
		ZA 7706063 A	28-06-1978
EP 100107 A	08-02-1984	AT 14846 T	15-08-1985
		CA 1158991 A	20-12-1983
		EP 0039504 A	11-11-1981
		EP 0099589 A	01-02-1984
		EP 0099590 A	01-02-1984
		EP 0099591 A	01-02-1984
		US 4552570 A	12-11-1985
US 5581903 A	10-12-1996	NONE	





1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100





Method and device for drying a gas

Patent number: EP1010452
Publication date: 2000-06-21
Inventor: LANG KRISTIAN KARL HENRIK (BE)
Applicant: ATLAS COPCO AIRPOWER NV (BE)
Classification:
- **International:** B01D53/26
- **European:** B01D53/26B
Application number: EP19980204242 19981214
Priority number(s): EP19980204242 19981214

Also published as:

 US6226888 (B)
 CA2292071 (A)

Cited documents:

 US5485686
 US4127395
 EP0100107
 US5581903

[Report a data error here](#)

Abstract of EP1010452

Method for drying a gas by means of adsorption on a regenerable desiccant (11), whereby a portion of the dried gas is used for regenerating the desiccant. The gas portion used for the regeneration is heated in at least two successive steps, said steps being performed in different zones (30,31 or 33-36) situated successively in the flow direction of the gas portion through the regenerating desiccant (11) and by stopping the heating in a zone (30,31 or 33-36) as soon as the desiccant (11) in this zone (30,31 or 33-36) is regenerated, so that this zone (30,31 or 33-36) may already be cooled down by the gas portion for regeneration while a successive zone (30,31 or 33-36) is still being regenerated by the heated gas. In each vessel (7,8) there are at least two individually controllable heating elements (25-26;27-28;38-41).




Fig. 2

Data supplied from the esp@cenet database - Worldwide

THIS PAGE BLANK

Docket # WBW-13036

Applic. # 10/534,682

Applicant: Wiedl et al.

Lerner and Greenberg, P.A.
Post Office Box 2480
Hollywood, FL 33022-2480
Tel: (954) 925-1100 Fax: (954) 925-1101